



SUPERFREEZE



**WE LET YOU
CONTROL THE ELEMENTS**

01 | Company Profile

A leading producer of Refrigeration Compressors, Evaporators, Controls and the largest manufacturer of Valves in India.

SUPERFREEZE is a leader in the industry & for more than three decades has contributed in areas like: Food Processing, Milk Dairies, Breweries, Sea Food industries, Pharmaceutical, Chemical plants, Power, Bulk Drugs, Fruits and Vegetables Cold Storage, Petrochemical, Fertilizers & Cryogenic industry.

The first in India to be **ISO 9001: 2000** certified in this niche segment, **SUPERFREEZE** is supported by a team of **200 highly skilled professionals** committed to delivering products & services to the highest standards.



“ We make an extra effort to deliver the finest customer experience and people know us for that. We believe in genuine quality and genuine”

Mr. Sanjeev Maini
(Chairman)




SUPERFREEZE's unique position as a leader can be attributed to its complete independence in terms of resources.

With two well equipped manufacturing units, independent un-interrupted power back up, in house foundries, machine shops and R&D labs the company surges from strength to strength with every product it manufactures.

SUPERFREEZE boasts of two advanced manufacturing facilities at Bahadurgarh and Nalagarh that are spread over a combined covered area of approx 100000 sq ft, and that house some of the finest machines.

The work force, committed and with evolved skill sets, tested over the years is also a major contributing factor to the quality of service & delivery at SUPERFREEZE.



03 | Quality Certification & Awards



Superfreeze maintains a high quality standard

throughout its manufacturing process to give its products the complete reliability edge. Every product manufactured, bears the unique stamp of precision, quality and functionality that Superfreeze is known for. An ISO certified company, its revolutionary contributions have been acknowledged world wide through numerous awards.



Superfreeze is driven by an urge to constantly improve, develop and innovate.

This culture at Superfreeze has led to the birth of revolutionary designs and products that are today positively impacting companies across the globe.

The Patented Stem Packing and Back Seat design, exclusive Superfreeze features are examples of this inspired approach. These have won Superfreeze accolades across the globe.



A socially conscious and environmentally aware company

it is committed to creating the ideal conditions for productivity. **SUPERFREEZE** walks the extra mile and provides residence facility for its work force within the premises. And as a strong believer in 'giving back to the society' **SUPERFREEZE** commits itself to a variety of programs:

Scholarship Programs: Empowering children through scholarship that covers every expense, creating conditions for a better tomorrow.

NGO Support: Support to organizations like LCRA and others that empower and work for the upliftment of the underprivileged.

Community Healthcare Services: Working closely with a team of dedicated doctors, **SUPERFREEZE** also sponsors community health drives to battle critical diseases like Cancer, Tuberculosis, HIV and Leprosy.



Features

- Rugged Design
- Patented Stem Packing and Back Seat Design
- Dual Stem Sealing
- Stainless Steel Stems
- Non Metallic Front and Back Seating
- Light Weight and Compact
- Hand wheel/ Seal cap option



SUPERFREEZE State-of-the-art Shut-off valves are designed specifically for use in industrial ammonia and large commercial halocarbon refrigeration systems.

Electronic Liquid Level Controller

Type: 38SLC

SUPERFREEZE liquid level controllers, type 38SLC are used to regulate the liquid level in a vessel or a flooded coil. The level controller consists of a float chamber and an electronic controller. A level indicator module is mounted on the controller consisting of LED's operating in bar graph mode. The indicator displays the rising and falling of liquid level inside the float chamber.

Specification

Refrigerants: R-717 (Ammonia), R-12, R-22, R-502 etc.

Differential: Adjustable between 10 and 50 mm

Media temp. Range: -45 °C to +55 °C

Max. operating pressure: 21 bar for float housing

Enclosure:

For float housing: IP65

For controller housing: IP55



Float Switch

Type: 38SFS

SUPERFREEZE Float switch, type 38SFS, is an electro mechanical float switch designed to provide a reliable, electro- mechanical response to liquid level changes. The design incorporates a mechanical float which will operate in the refrigerant. When the set level is reached an electrical volt free micro switch will be activated.

Specification

Refrigerants: R-717 (Ammonia), R-12, R-22, R-502 etc

Safe Operating Pressure: 406 psig (28 bar)

Operating Temperature Range: -50 °C to +65 °C

Liquid level differential: Variable between 12.5mm to 50mm (1/2" to 2") in 12.5mm (1/2") increments

Normally Open (NO) and Normally Closed (NC) function

Enclosure: IP65



Solenoid Valves

Type: SFA

The primary purpose of an electrically operated Solenoid valve is to control automatically the flow of fluids, liquids and gasses.

SUPERFREEZE SFA - Series Solenoid valves may be applied on a wide variety of applications. These flanged, industrial refrigeration duty solenoid valves are very simple and compact but rugged in construction. These are direct acting or pilot operated solenoid valves for liquid suction and hot gas lines with ammonia or fluorinated refrigerant.

Specification

Temperature of medium: -40 °C to +80 °C with 18 Watt coil

Safe Working Pressure: 300 psig (21 bar)

Refrigerants: Suitable for all common refrigerants including R-717 (Ammonia), R-12, R-22, R-134a, R-502

Coil : Same for all Superfreeze SFA-Series Solenoid Valves



Regulating Valves

Type: SPR1 & SPR3

Port Size: 32mm, 40mm, 50mm, 65mm, 75mm & 100mm

Connections: Butt Weld

SUPERFREEZE regulating valves types SPR1 & SPR3 are specially designed for capacity regulation in refrigeration, freezing and air conditioning plant for ammonia and fluorinated refrigeration.

Specification

Refrigerants: R-717 (Ammonia), R-12, R-22, R-502 etc

Media temperature range: -50 °C to +120 °C

Max. operating pressure: 28 bar

Max. test pressure: 42 bar

- Pilot:**
- Solenoid Pilot Valve
 - Pressure Controlled Pilot Valve
 - Temperature Controlled Pilot Valve
 - Differential Pressure Controlled Pilot Valve




Stop Valves

Type: SBW

Port Size: 6mm thru 10mm Globe and Angle type

Connections: Butt weld

SUPERFREEZE stop valves are simple in construction and rugged for industrial use. These valves are equipped with union nut for ease of replacement and provided with weldable nipple.



Gauge Valves

Type: SPGV

Port Size: 8mm, 10mm & 12mm weldable

SUPERFREEZE Gauge valves are simple in construction and rugged for industrial use. These valves are equipped with union nut for ease of replacement and provided with weldable nipple.



Digital Temperature Indicator

Type: SFT21

Specification

Dial Size: 4" with 1" display

Input Sensor: RTD PT100

Range: -50 °C to +50 °C
-60 °F to +95 °F

Probe Wire Length: 5mtr

Supply: 230V AC



Weld -in- Line Stop Valves

Type: SSW
Port Size: 1/2" thru 2" (15mm – 50mm) for Straight and Angle form
Connections: Socket Weld

SUPERFREEZE SSW - Series well designed and constructed **low pressure** drop refrigerant shut-off valves are welded directly to steel piping, thereby eliminating potential leaky flanges or threaded joints and simplifying installations.

Specification

Refrigerants: Suitable for all common refrigerants including R-717 (Ammonia), R-134a, neutral, gaseous and liquid media

Temperature Range: -46 °C to +116 °C (-50 °F to +240 °F)

Temperature Below: -60 °F at lower pressure

Safe Working Pressure: 568 psig (40 bar) PS-40 Rated

Leak Proof Sealing : Non Metallic special polymer seal and taper seat provides leak proof sealing.

Back Seating & Gland Packing:

The heart of **SUPERFREEZE** shut-off-valve is the **Patented Stem Packing & Backseat Design**. This Patented design is used exclusively on **SUPERFREEZE** valves & virtually eliminates stem leakage.

Light Weight & Compact : Ease of installation

Stem: Stainless Steel

Flow : Can accept flow in both direction

Available in both wheel and vented cap option



Weld -in- Line Stop Valves

Type: SBW
Port Size: 1/2" thru 12" (15mm – 300mm) for globe and angle form
Connections: Butt Weld

SUPERFREEZE SBW - Series well designed and constructed low pressure drop refrigerant shut-off valves are butt-welded directly to steel piping, thereby eliminating potential leaky flanges or threaded joints and simplifying installations.

Specification

Refrigerants: Suitable for all common refrigerants including R-717 (Ammonia), R-134a, neutral, gaseous and liquid media

Temperature Range: -46 °C to +116 °C (-50 °F to +240 °F)

Temperature Below: -60 °F at lower pressure

Safe Working Pressure: 568 psig (40 bar) PS-40 Rated

Leak Proof Sealing: Non Metallic special polymer seal and taper seat provides leak proof sealing.

Back Seating & Gland Packing:

The heart of **SUPERFREEZE** shut-off-valve is the **Patented Stem Packing & Backseat Design**. This Patented design is used exclusively on **SUPERFREEZE** valves & virtually eliminates stem leakage.

Light Weight & Compact: Ease of installation

Stem: Stainless Steel

Flow: Can accept flow in both direction

Available in both wheel and vented cap option



Stop Valves

Type: FSV (Flanged connections)

Port Size: ½" thru 4" (15mm – 100mm) for flanged connections.

Type: SSV (Screwed connections)

Port Size: ¼" thru 2" (6mm – 50mm) for screwed connections.

The advanced design and material of **SUPERFREEZE** FSV - Series stop valves make them a far superior product, especially in regards to non leakage of seat, bonnets and back seating.

All valves are available in Straight and Angle form.



Specification

Refrigerants: R-717 (Ammonia), R-12, R-22 & other common refrigerants.

Temperature Range: -46 °C to +116 °C (-50 °F to 240 °F)

Safe Working Pressure: 365 psig (21 bar)

Leak Proof Sealing: Non Metallic special polymer seal and taper seat provides leak proof sealing.

Back Seating & Gland Packing:

The heart of **SUPERFREEZE** shut-off-valve is the **Patented Stem Packing & Backseat Design**. This Patented design is used exclusively on **SUPERFREEZE** valves & virtually eliminates stem leakage.



Check Valves

Type: PSCK1

Port Size: 1¼" thru 6" (32mm – 150mm)

Connections: Flanged

SUPERFREEZE PSCK - Series piston type, gravity closing, heavy duty check valves are suitable for ammonia R-12, R-22 and other refrigerants. All PSCK check valves are flanged and have a provision for manual operation with the help of manual opening stem. The PSCK valves have metal to metal seats.

Application:

The PSCK piston-type check valves prevents backward flow of refrigerant in liquid, discharge, and suction and hot gas lines. They are recommended for compressor discharge lines and also for liquid line & suction lines with the temperature as low as -30 °C (-25 °F)



Stop Cum Check Valves

Type: WSCK2

Port Size: ½" thru 6" (15mm – 150mm) for globe and angle form

Connections: Butt Weld : ½" thru 6" (15mm – 150mm)

Socket Weld : ½" thru 2" (15mm – 50mm)

SUPERFREEZE well-designed and constructed low pressure drop refrigerant stop cum check valves are butt-weldable directly to steel piping, thereby eliminating potential leaky flanges or threaded joints, and simplifying installation. The important features of these valves are non leak packing and back seat design. In valve open condition, if inlet pressure drops below outlet pressure, the valve acts as check valve and do not allow reverse flow of liquid.

Specification

Refrigerants: Suitable for all common refrigerants including R-717 (Ammonia), R-134a, R-404, neutral, gaseous and liquid media

Temperature Range: -46 °C to +116 °C (-50 °F to +240 °F)

Temperature Below: -60 °F at lower pressure

Safe Working Pressure: 365 psig (25 bar)

Available in both wheel and vented cap option

Available in angle and straight types

Applications:

Ammonia refrigeration system suction, liquid discharge, recalculating liquid, hot gas and oil lines, using hand wheel of seal cap models and also compressor suction, discharge connections, condenser, evaporator inlet and outlet connections in ammonia, R-22, R-134a and other approved refrigerant.



Strainer Valves



Type: STW
Port Size: ½" thru 12" (15mm – 300mm)
Connections: Butt Weld



Type: STA
Port Size: ½" thru 1¼" (15mm – 32mm)
Connections: Flanged



Type: SST
Port Size: ½" thru 6" (15mm – 150mm)
Connections: Flanged



Type: SST
Port Size: ½" thru 1" (15mm – 25mm)
Connections: Screwed

SUPERFREEZE Strainers are designed for either liquid or suction line application. They provide free flow with negligible pressure drop and can be used for a variety of liquids.

All **SUPERFREEZE** Strainers contains the maximum effective screen area. Screen assemblies are seam welded, and the ends reinforced or capped with seal rings. This construction reduces the possibility of bursting the screen assembly. The end of the screen assembly seats against the flange plate to form a tight seal, thereby preventing dirt from bypassing the strainer screen.

All cleanable strainers have an access for easy removal of the screen assembly. This facilitates cleaning and inspection without breaking the line connection.

Strainers are usually close-coupled to solenoid valves, pressure regulators and other flanged valves.

Specification

Refrigerants: R-717 (Ammonia), R-12, R-22, R-134a and other common refrigerants.

Screen: Stainless Steel, 70 Mesh /40 Mesh

Safe Working Pressure: 365 psig (25 bar)

Gauge Angle Valves

Type: SGV
Port Size: ½" x ¾" (15mm x 20mm) (inlet x outlet)
Connections: Screwed ends.

SUPERFREEZE SGV - Series are used along with a toughened glass tube for liquid level indication in receivers and accumulators. One pair of valves are used for one set of liquid level indicator. If the glass breaks by some sudden impact, the ball inside the valves stop the refrigerant flow immediately.





Hand Expansion Valves

Type: SEV

Port Size: ¼" thru 1" (6mm – 25mm) for globe and angle form, screwed end.

Port Size: ½" thru 2" (15mm – 50mm) for globe and angle form, flanged end.

SUPERFREEZE SEV - Series precision calibrated adjustable seat nut flow regulating valves (expansion valves) are ideal for metering or flashing expansion of liquid refrigerant. These slotted seat nut are more tolerant to dirt particle than tapered plug expansion. Hand wheels are of red color to distinguish them from shut-off valves. Suitable for R-717 (Ammonia), Halocarbons.



Flow Indicators

Type: SFI

Port Size: 1" thru 2" (25mm – 50mm)

Connections: Flanged and Butt Weld.

SUPERFREEZE SFI - Series provides a quick, reliable and economical way to verify the flow of refrigerant in refrigeration system.

Applications:

It is suitable for R-717 (Ammonia), R-22, R-134a and also other approved refrigerants. It is used in refrigeration system pipeline.



Self Closing Oil Drain Valves

Type: SODV

Connection Size: ½" Sh 40 Butt weld with Union Nut

SUPERFREEZE SODV - Series quick closing oil drain valves are used for draining oil from systems containing refrigerant under pressure. The main feature of this valve is that on release of the handle the valve closes immediately, thus protecting the user from unnecessary refrigerant leaks.

Features:

Spring loaded quick closing action

Stainless steel stem



Reflex Glass Liquid Level Indicator

Type: SLLI

SUPERFREEZE SLLI - Series the unbreakable Reflex Glass Liquid Level gauge is designed for safe & positive visual indication of liquid level in vessels under high pressure & temperature conditions. The liquid chamber is one piece metal body covered by glass. The light striking the glass in the liquid portion is absorbed by the liquid where as the light striking the glass in the vapor portion is reflected making the liquid appear as black.

Specification

Suitable for all common Refrigerants including R-717 (ammonia), R-134a, R-22, neutral, gaseous & liquid media.

Tempered borosilicate glass resistant to chemical, thermal and mechanical shocks.

Large chamber for boiling, flashing or surging liquids.

Safety ball gauge valve provided.

Standard sizes available 6", 12", 18", 24", 30", 36", 42", 48", 54", 60".



Flanges



Type: SWF

Port Size: ½" thru 12" (15mm thru 300mm)

Specification

Suitable for all common refrigerants including R-717 (Ammonia), R-22, R-134a
Safe working pressure : 365 psig (25 bar)
Available with socket weld connection
Tongue and Groove type

Air Cooling Units



Applications:

Our Air Cooling Units are best suited for Potato/ fruit/ vegetable cold storages, milk processing units and meat/ fish/ ice cream/ butter freezing units.

Features:

Coils made of heavy duty precision tubes and aluminum fins. The tubes are galvanized on the outside and bullet expanded with automatic machine into the fins for excellent bonding between them. Aluminum fins ensures rapid heat absorption from air. The staggered tube construction increases air turbulence at the coil to increase efficiency. VAR-FIN arrangement to reduce frosting at low temperatures.

Weather proof motors with IP-55 enclosure.

Accumulator (surge drum) to protect liquid stroke to compressor.

Arrangement for both ceiling suspension and floor mounting on every coil as standard.

Water defrosting headers for low temp. coils.

Optional Features (At extra cost):

Hot dip galvanized coil with steel tubes and steel fins.

Hot gas defrosting arrangement.

Drain-pan with heating coil.

Custom Build coils for special applications.

13 | Testimonials



"Our association with Superfreeze has been a mutually beneficial one, giving us both quality products and committed services. We are glad that we have a partner in Superfreeze."

D.B.Sonawane
(Manager Purchase Engg.)
Frigerio Conserva Allana Limited



"We have been using Superfreeze valves since long in many of our projects and we appreciate their commitment to prompt delivery and unwavering quality. We look forward to a long business association with them."

GG Diwan
ACR Engineering Sales & Services



"It has been an eight year long association with Superfreeze for us. They have been dependable in their services proving reliable throughout their meticulous processes. We look forward to their association in the future."

(Managing Director)
Tirumala Milk Products Pvt. Ltd.



"We have been using Superfreeze weldable flanged valves for quite some time now and their performance has always been up to the mark."

Rajesh Subramaniam
IDMC Limited



"Superfreeze has provided us compressors, compressor spares, valves & fittings for over 10 years and we are very satisfied with their products and services."

Porus Laboratories



"Superfreeze has supported us through their Ammonia Compressors, spares, Valves & Fittings for the past 8 years and they have delivered the finest in quality and performance all along."

Auctus



"For over a decade we have been using Superfreeze ammonia valves, fittings & spares and are immensely happy with their products and services. We also appreciate their attention to quality and their adaptability to our specific requirements. It has been a great pleasure doing business with them."

Hitesh Chemicals & Drugs Pvt Ltd.



"We have been associated with Superfreeze for more than 15 years now. Their Weldable & Flanged and Screwed valves that are installed in our ice cream Plants have always given us great performance."

Pankaj Trivedi (GM Engg)
Havmor



"We use Superfreeze make ammonia refrigeration valves in our projects and we have always found their products and services satisfactory. We also appreciate their timely deliveries and their consistent quality. Looking forward to a long term business association with them."

Jayant Deshpande
VOLTAS



"The Superfreeze valves that we use for refrigeration in our projects like Parag Milk, Rich Graviss and Gomati Milk etc, have always been of the finest quality. We would like a continued business relation with Superfreeze and are appreciative of their commitment to prompt delivery and exceptional services."

Refcon Engineering Services



"We have been associated with Superfreeze for well over a decade now and all we can say is that they have consistently been outstanding in their performance. Their level of understanding our business and delivering quality services is marvelous. We hope to continue this association for years to come."

(Senior Manager Engineering)
Creamline Dairy Products Ltd.



"We have been acquiring Ammonia Globe Valves, Check Valves, Needle Valves & Safety Valves, for our Dairy & Food projects from Superfreeze on a continued basis & we are pleased to inform that every time, Superfreeze has only provided the highest quality of services & products. It has always been a great customer experience working with them."

B.K. Aswathnarayan
Bekay Engineering Services


Taking pride in the sterling contributions we make to some of the biggest names, at home...

UB Group, Pepsico, Coca-Cola, Cadburys, Nestle, Vadilal, Cipla, Kwality Wall's, Ranbaxy, AL Kabeer, Amul, Novartis, Larsen & Toubro, Thermax, Voltas, Tetra Pak, Alfa Laval, Smith Kline Beecham, Sabroe, IDMC, Blue Star, York India, Alembic, ACR, Milkfed Punjab and a whole range of other names, representing almost every conceivable domain.



...and Abroad

USA | Australia | U.A.E | Chad | Bangladesh | Nepal



Member :





SUPERFREEZE INDIA (P) LTD

An ISO 9001 : 2015 Certified Company

122, Qutab Plaza, DLF Phase-I, Gurgaon -122002, Haryana, India

Tel : +91-124-4301636

E mail : sales@superfreeze.com Website : www.superfreeze.com

Disclaimer

- a) We reserve the right to modify specifications in accordance with improved designs. Although every effort will be made to maintain accuracy in the data given, the figures must be taken as approximate and in no way binding. The claims are as per our knowledge and for any variance we are not bound in any way.
- b) The customer trade marks shown here-in are properties of respective companies.